

IN THE CLAIMS :

Amend Claims 1-17 as follows and add Claims 18-20:

1. (Currently Amended) Device to transmit power from a power system (28) of a working machine (1) to one or more moving parts (25, 26) of a tool (3-5) replaceably attachable to a first part of the working machine which is in the form of a beam, or such, wherein ~~characterized in that~~, it comprises a first element (7) arranged on the working machine and driven by its power system, a second element (11) movably attached to the tool and means (8, 12) arranged to mechanically interconnect both of said elements so that a displacement of the first element via the working machine's power system brings about a movement of the second element on the tool.

2. (Currently Amended) Device according to claim 1, wherein ~~characterized in that~~, said means (8, 12) for mechanical interconnection is arranged to automatically establish a mechanical interconnection of the first (7) and second (11) elements on attachment of the tool to the working machine's first part.

3. (Currently Amended) Device according to claim 2, wherein ~~characterized in that~~, the means for mechanical interconnection comprise engagement means (8, 12) on the first and second elements, which are arranged to co-operate with each other to automatically establish power-transmitting engagement with each another on attachment of the tool to said first part.

4. (Currently Amended) Device according to claim 3, wherein ~~characterized in that,~~ one of the engagement means is formed from a projection (12) arranged on the first element and the other engagement means is formed from a recess (8) arranged on the second element and arranged to receive the projection on moving the tool and the first part together.

5. (Currently Amended) Device according to claim 2 ~~any of the claims 2-4,~~ wherein ~~characterized in that,~~ the second element (11) is displaceably arranged in a track on the tool via power transmission from the first element (7).

6. (Currently Amended) Device according to claim 1 ~~any of the preceding claims~~ wherein ~~characterized in that,~~ it comprises an arrangement (13, 16, 17) for interconnection of the second element (11) with said moving parts (25, 26) of the tool to transmit a movement of the second element to a movement of these tool parts.

7. (Currently Amended) Device according to claim 1 ~~any of the preceding claims,~~ wherein ~~characterized in that,~~ it comprises a pressure medium cylinder (9) arranged on said first part of the working machine near an attachment arrangement for the tool, and connected to the working machine's power system (28), and ~~that~~ said first element (7) is formed from, or connected to, a part of said cylinder that is moveably arranged relative to the first part.

8. (Currently Amended) Device according to claim 7, wherein ~~characterized in that,~~ the first element (7) is formed from an end of a piston rod of the cylinder which is distant from the piston.

9. (Currently Amended) Device according to claim 7 ~~or 8~~, wherein characterized ~~in that~~, the pressure medium cylinder (9) is a hydraulic cylinder connected to the working machine's power system (28) that is in the form of a hydraulic system.

10. (Currently Amended) Device according to claim 1 ~~any of the preceding claims, wherein characterized in that~~, said second element (11) is arranged to operate a drive unit to set parts (25, 26) of the tool into motion relative to a body (24) of the tool on displacement of the second element relative to the body of the tool.

11. (Currently Amended) Device according to claim 10, wherein characterized ~~in that~~, said second element (11) is connected to a second pressure medium cylinder (13) on the tool, which lacks a power supply through any pressure medium source to cause movement of the piston (14) of this second cylinder relative to a casing of the cylinder by movement of the first element (7).

12. (Currently Amended) Device according to claim 11, wherein characterized ~~in that~~, the second pressure medium cylinder (13) is arranged to function as a pump to drive one or more additional pressure medium cylinders (16, 17) arranged on the tool, which are in pressure medium flow communication with the second cylinder.

13. (Currently Amended) Device according to claim 6 ~~and possibly any of the other preceding claims, wherein characterized in that~~, the tool is a fork unit with forks (25, 26) that are laterally displaceable along a frame (24), and ~~that~~ the interconnection arrangement is arranged to transmit a movement of the second element (11) to a movement of the forks.

14. (Currently Amended) Device according to claim 12 ~~and 13~~, wherein ~~characterized in that~~, it comprises two said additional pressure medium cylinders (16, 17) for driving a fork (25, 26) each.

15. (Currently Amended) Device according to claim 14, wherein ~~characterized in that~~, both of said additional pressure medium cylinders (16, 17) have mutually interconnected pressure medium chambers to make a movement of one fork (25) dependent on a movement of the other fork (26).

16. (Currently Amended) Device according to claim 15, wherein ~~characterized in that~~, said additional pressure medium cylinders (16, 17) are interconnected to cause a displacement of the forks (25, 26) in opposite directions for separating or bringing them together relative to each other via movement of the second element (11).

17. (Currently Amended) Device according to claim 15, wherein ~~characterized in that~~, both of said additional pressure medium cylinders (16, 17) are interconnected to cause a displacement of the forks (25, 26) in the same direction for simultaneous displacement thereof to one side or the other of a body of the tool via movement of the second element 11.

18. (New) Device according to claim 3, wherein the second element (11) is displaceably arranged in a track on the tool via power transmission from the first element (7).

19. (New) Device according to claim 4, wherein the second element (11) is displaceably arranged in a track on the tool via power transmission from the first element (7).

20. (New) Device according to claim 19, wherein it comprises an arrangement (13, 16, 17) for interconnection of the second element (11) with said moving parts (25, 26) of the tool to transmit a movement of the second element to a movement of these tool parts.